



Coaxial Circulator, 1200-1400MHz N-Type Connector, 300 Watts, 10 kilowatt Peak RADC-1200-1400M-N23-300WR(10kW Peak)



Tolerance (unless otherwise stated):

Hole diameter	±0.004
Dimensions	±0.015
Machined surfaces	63√
Flatness	±0.001/inch
Bend radius	1/32 inch



Direction of RF:

R	Default	
L		

Units: mm
Not to scale

Order Examples: RADC-1200-1400M-NX-300WR(10kW Peak)
I=ISOLATOR / C=CIRCULATOR

N / SMA Connector options (X)				
Isolator			Circulator	
Port 1	Port 2		Port 3 Male	Port 3 Female
Female	Male	-1	-11	-21
Male	Female	-2	-12	-22
Female	Female	-3	-13	-23
Male	Male	-4	-14	-24

Size#	A	B	C	D	E	F	H	I	L	
1	75.184	75.184	27.9	tba	tba	tba	tba	tba	tba	mm
										mm

Size#	Specifications: Frequency MHz	Insertion loss dB (max)	Isolation dB (min)	VSWR :1	Avg Power Watts	Peak Power kWatts	Temp °C	Connector
1	1200-1400	0.25	20	1.20	300	10	-10 to +50	N-Type