ROHS Compliant

RADITEK INC.

code-b

Coaxial Isolator, 2.13-2.30GHz, Split Bands
SMA Connector, 10 Watts
RADI-2.13-2.23-S3-10WR





Tolerance (unless otherwise stated):

Hole diameter	±0.004
Dimensions	±0.015
Machined surfaces	63√
Flatness	±0.001/inch
Bend radius	1/32 inch



Direction of RF:	
R	Default
L	

Units: mm
Not to scale

Order Examples: RADI-2.13-2.23-S3-10WR
I=ISOLATOR / C=CIRCULATOR

N / SMA Connector options (X)				
Isolator			Circulator	
Port 1	Port 2		Port 3 Male	Port 3 Female
Female	Male	-1	-11	-21
Male	Female	-2	-12	-22
Female	Female	-3	-13	-23
Male	Male	-4	-14	-24

Size#	A	B	C	D	E	F	H	I	L	
1	25	30	20	tba	tba	tba	tba	tba	tba	mm
										mm

Size#	Specifications: Frequency GHz	Insertion loss dB (max)	Isolation dB (min)	VSWR :1	Power Fwd Watts	Power Rev Watts	Temp °C	Connector
1	2.13-2.23	0.5	25	1.25	10	10	-20 to +60	SMA
1	2.20-2.30	0.5	25	1.25	10	10	-20 to +60	SMA

WORLD HQ: 1702L Meridian Ave. Suite 127, San Jose, Ca 95125, U.S.A.
Telephone: (408) 266-7404 FAX: (408) 266-4483
WEB: www.raditek.com , E-mail: sales@raditek.com