



Octave Band Isolators and Circulators RADI-4-8-N3-150WR-b



RADITEK's Octave Band Isolators and Circulators are a cost effective solution for wide band frequency applications. This model covers 4.0-8.0 GHz with 150 Watts of reverse power and 150 Watts of Forward Power. Power Options available are: 110, 150, 200 and 250Watts. Other Popular frequencies, 500-1000MHz, 1500-3000MHz, 1.0-2.0GHz, 2.0-4.0GHz, 3.0-6.0GHz, 4.0-8.0GHz, 6-12GHz and 8.0-18GHz. Octave Plus and Peripheral Mode units also available. Typical Specifications: 0.4dB Insertion Loss, 18dB Isolation, VSWR 1.3:1. Operating Temp. -30~+70°C. Dimensions: 83 (W) x 55.2 (L) x 21.5 (H) mm. These units are proven in the field and are fully ROHS compliant.

RADITEK specializes in RF Design and Development of "High Volume / Low Cost" Microwave, Wireless and Telecom Broadband Components, Assemblies and Systems. Please see our website at http://www.Raditek.com or email us at Sales@Raditek.com with any questions you may have.

WORLD HQ: 1702L Meridian Ave. Suite 127, San Jose, Ca 95125, U.S.A. Tel: (408) 266-7404 FAX: (408) 266-4483

WEB: www.raditek.com E-mail: sales@raditek.com