

# Vehicle Mounted Antenna

C Band , 1.8 Meter Rx-Tx

Carbon Fiber Reflector

### Features

- ❖ Reflector: 1.8 meter Carbon Fiber
- ❖ Feed: Precision Horn
- ❖ Optics: Offset, Prime Focus
- ❖ Az/EI Drive System: Patented
- ❖ Mount Geometry: Elevation over Azimuth
- ❖ Polarization Adjustment: Rotation of Feed



# RADITEK

**SATCOM**  
Vehicle Mounted Antenna

**Order Examples:** RVMA-1.8m-CFR-v9

**Description:** (Vehicle Mount Antenna System, C Band, 1.8 Meter diameter, Carbon Fiber reflector)

Specifications: Electrical RF	Receive	Transmit
Frequency	3.625 – 4.2 GHz	5.850 – 6.425 GHz
Gain (Midband)		
2-port	35.5 dBi	39.5 dBi
VSWR	1.30:1	1.30:1
<b>Beamwidth (degrees)</b>		
-3 dB	3.0	2.0
-10 dB	5.1	3.3
First Sidelobe Level (Typical)	-16 dB	-16 dB
<b>Radiation Pattern Compliance</b>		
Transmit – 1.5° to 30°		29-25 Log Ø
Receive – 2.4° to 30°	32-25 Log Ø	
Antenna Noise Temperature	45° K at 10° Elevation	
Polarization	Linear Standard, Optional Circular	
Power Handling Capability		1KW per port
<b>Cross-Pol Isolation – On-axis</b>		
Linear	35 dB	35 dB
Circular	19 dB	25 dB
Feed Port Isolation – TX to RX	70 dB	
<b>Satellite System Compliance: Compatible for 2° Satellite Spacing</b>		
<b>Controller</b>		
Standard	Three-axis Jog Control & Display with Auto-stow	
Optional Upgrades		
Semi-automatic Operation	Moves to calculated position based on operator entered vehicle location, heading, plus satellite (longitude or listed)	
Automatic Operation	Moves to calculated position based on auto GPS and Flux-Gate Compass data and satellite peaking with LNB signal	
Size	Two Rack Units for Semi-Automatic & Automatic Controllers	
Input Power	110/240 VAC, 1 phase, 50/60 Hz, 10/5 A peak, 1A continuous	

## Vehicle Mounted Antenna C Band, 1.8 Meter Rx-Tx

<b>Mechanical</b>	
Az/EI Drive System	Patented Roto-Lok® Cable Drive System
Polarization Drive System	Rotation of Feed
<b>Travel</b>	
Azimuth	400° with all 2-port and 4-port with HPA(s) on antenna, 270° Standard with 4-port and HPA(s) in Vehicle
Elevation	True elevation readout from calibrated inclinometer
Mechanical	0° to 90° of Reflector Boresight
Electrical	Standard limits at 5° to 65° (CE Approval) or 5° to 90°
Polarization	±95° for 2-port and 3-port Feeds ±50°, 100° Effective for 2-port Wideband and 4-port feeds
<b>Speed</b>	
Slewing/Deploying	2°/second
Peaking	0.1°/second
Motors	24V DC Variable Speed, Constant Torque
<b>RF Interface</b>	
HPA Mounting	Feed Boom, Rear of Reflector or Inside Truck
Axis Transition	Rotary Joints in Az, EI, and Pol
Waveguide	WR 137 Flat Flange at center of azimuth axis WR 229 Flat Flange at feed omt
Coax	RG59 run from feed to base plus 25 ft. (8 m)
Electrical Interface	25 ft. (8 m) Cable with Connectors for Controller
Manual Drive	Handcrank on Az and EI Axii, Leads from 12VDC Pol Motor
Weight	275 lbs. (125 kg)
Stowed Dimensions	100 L x 74 W x 20 H inches (254 L x 188 W x 58 H cm)
<b>Environmental</b>	
Wind	
Survival	
Deployed	80 mph (128 kmph)
Stowed	125 mph (201 kmph)
Operational	45 mph (72 kmph), Gusts to 60 mph (97 kmph)
Pointing Loss in Wind	
20 mph (32 kmph)	0.1 dB max
30 Gusting to 45 mph (48 to 72 kmph)	0.4 dB max
Temperature	
Operational	20 to 125°F (-29° to 51° C)
Survival	-40° to 140°F (-40° to 60° C)