


Voltage Controlled Oscillator, 1.0-2.0GHz, 10dBm Power Output, 15 Volts, TO-8 Package



Order Examples: RVCO-1.0-2.0-10d-15V-TO-8-s7

Description: (Voltage Controlled Oscillator, 1.0-2.0GHz, 10dBm Power Output, 15 Volts, TO-8 Package, s7-Model)

Electrical Specifications: ⁽¹⁾

Parameter	Specifications
Frequency Range	1.0 to 2.0 GHz
Power Output at 25°C (50 Ohm load)	+10 dBm, min.
Power Output Variation vs. Temperature	2.0 dB, typical
Frequency Drift vs. Temperature ⁽²⁾	55 MHz, typical
Frequency Pulling (12 dB Return Loss)	18 MHz, typical
Frequency Pushing	2.0 MHz/V, typical
Tuning Voltage Limits	0 to +20 VDC
SSB Phase Noise (50 kHz offset)	-105 dBc/Hz, typical
Harmonics ⁽³⁾	-14 dBc, typical
Spurious	-70 dBc, max.
Bias Voltage ⁽⁴⁾	+15 VDC ±1%
Bias Current ⁽⁵⁾	50 mA, typical
Operating Temperature	-55 to +85°C

Notes:

- Specifications guaranteed over the operating temperature range. Those specifications indicated as typical are not guaranteed. Plots exemplify typical performance at +25°C
- Total frequency drift over the full temperature range.
- Worst case harmonics over the frequency range.
- Alternate bias voltages available.
- Lower bias current available.
- Military screening available.

Typical Performance at 25°C

